

Cleanroom KL Tear Drop

Sealed 4' Linear Teardrop LED Luminaire. Surface Mounting to T-Bar Grid

- **Suitable for ISO 3-9 Cleanspaces**
- **Suitable for 209E 1-100,000 Cleanspaces**
- **ETL Listed for Wet Locations**
- **Suitable for Row Mounting with CRM option**
- **Luminaire mounts directly to Tbar Grid.**
- **Available with 590nm True Amber LEDS.**
- **Luminaire profile specifically designed for a low drag on laminar air flow applications**
- **B.A.A. & B.A.B.A Compliant & Made in the USA by a Family Owned US Corporation**



DISCLAIMER: Although KURTZON has prepared the information contained in this document with all due care, KURTZON does not warrant or represent that the information is free from errors or omission. Whilst the information is considered to be true and correct at the date of publication, changes in circumstances after the time of publication may impact on the accuracy of the information. The information may change without notice and KURTZON is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

ORDERING GUIDE

Series	Material	Size	Row Qty.	LED Type	CCT/CRI	Voltage	Optics	Options
KL-AFV			1					

Series	Material	Size	Light Source			Voltage	Optics	Options
			Row Qty.	LED Type	CCT/CRI			
KL-AFV	1 White CRS Ext. & White CRS Int.	40' 4" Housing	1	LEDR (White)	83 CRI:	120V	PA Linear Prismatic Clear Acrylic	PxL * Programmed to User Specified Lumen Value.
				LEDH (White)	830 3000K	277V	FA Linear Frosted Acrylic	PxW * Programmed to User Specified Wattage Value.
	2 Polished 304 SS Ext. & White CRS Int.			YLED590 (Amber)	835 3500K	UNV		10KV 10KV Parallel Surge Protection (One Supplied Per Circuit)
					840 4000K	347V*		WHIP Must Specify Length and Wire Qty
					850 5000K			FC Fuse & Holder (One Supplied Per Circuit)
	3 Polished 304 SS Ext. & Polished 304 SS Int.				90+ CRI:			EM10 10W Integral LED EM (Specify Input Voltage)
					935 3500K			EDL -40F Electronic Driver
					940 4000K			AMW Anti-Microbial White Powdercoat
					950 4000K			TP Torx Head SS Tamperproof Fasteners
								CRM Continuous Row Mounting
								WHT White Finished Stainless Steel

Note*: Specify Value in Ordering Notes Below

Ordering Notes, If Applicable

Cleanroom KL Tear Drop

Sealed 4' Linear Teardrop LED Luminaire. Surface Mounting to T-Bar Grid

SPECIFICATIONS

HOUSING: Double channel housing of 20Ga Cold Rolled Steel or 20Ga 304 Stainless Steel.

END CAPS: Precision stamped 20Ga 304 Stainless Steel end caps secured to housing with captive stainless steel pan head screws. See Options for Tamper resistant Torx drive stainless steel fasteners or hub assembly.

GASKETS: NSF Listed closed cell microcellular extruded KleanLock SealPro gasket with vulcanized corners making a one-piece oil and solvent resistant gasket system.

OPTICS: Available in extruded .125" Thick Clear or Frosted Acrylic.

LEDs: Commercially available in a wide variety of Color Temperature (CCT), FLUX, and CRI. Highly efficient and consistent color maintained to 3 SDMC for color critical applications. B50/L70 and compliant with Zhaga recognized hole patterns. Consult factory for LED options or configurations not listed below.

DRIVERS: Standard Universal Voltage Class 2 drivers are 0-10v Dimmable to 1% and rated -20C (-4F). They come with at least 2.5Kv surge protection, have less than 10% THD at max load, Ballast Factor Greater than .95 and are programmable to match specific lumen or wattage requirements. Drivers with higher input voltage ratings are available, consult factory for driver specifications.


REFLECTOR: Die formed metal with high reflectance white polyester powder coat finish. Typical reflectivity 92%.

INSTALLATION: Two .312" holes for surface mounting. Supply entry through back side of housing. Joiner bands provided for continuous row mounting (See Option: CRM). Please specify number of fixtures in each run. Suitable for surface installation onto covered ceiling only.

FINISH: Stainless steel housings are satin polished unless WHT or AMW options are selected. All other materials are provided with gloss high reflectance white polyester powder coat with 1000hr salt spray test per ASTM B117. AMW options provides a white anti-microbial polyester powder coat to all exposed metal surfaces.

LISTINGS: ETL listed per UL_1598 for wet locations. Certified ISO-14644-1 for class 3 through class 9 cleanspaces. Certified Fed Std 209E for Class 1 through Class 100,000 cleanspaces. Drivers and LEDs are covered by a 5 year warranty, the remaining fixture is covered by a 10 year warranty. This product Series is both Build America Buy America (B.A.B.A.) & Buy American Act (B.A.A.) compliant.

PRODUCT DRAWINGS



Cleanroom KL Tear Drop

Sealed 4' Linear Teardrop LED Luminaire. Surface Mounting to T-Bar Grid

ENERGY DATA

TEARDROP PROFILE LED (APPROX ¹ LUMENS DELIVERED)								
ENCLOSURE SIZE	LIGHT PACKAGE	CRI OR COLOR	DIMMING	FROSTED LENS			AMBIENT TEMP RATING	
				LUMENS	WATTS ²	EFFICACY ³ (Lm/W)	MINIMUM	MAXIMUM ⁴
40	1LED R	83	0-10V 1%	3,704	29	127	-20°C (-4°F)	40°C (104°F)
40	1LED R	90+ CRI	0-10V 1%	3,575	29	123	-20°C (-4°F)	40°C (104°F)
40	1LED H	83	0-10V 1%	6,735	53	127	-20°C (-4°F)	40°C (104°F)
40	1LED H	90+ CRI	0-10V 1%	6,500	53	123	-20°C (-4°F)	40°C (104°F)
40	1YLED	590nm AMBER	0-10V 1%	1,600	43	37	-20°C (-4°F)	40°C (104°F)

- ¹ DELIVERED LUMEN DATA IS EXTRAPOLATED FROM MEASURED DATA @25C WITH NO EXTRA OPTIONS. VARIANCES WILL OCCUR WHEN OTHER SELECTIONS ARE MADE
- ² WATTAGE IS MEASURED WITH LED 840 SELECTION @ 120vAC AND Tambient = 25C. WATTAGES WILL VARY AND INCREASE WHEN ALTERNATE OPTOINS ARE SELECTED
- ³ EFFICACY CALCULATED USING 80 CRI 4000K CCT DATA.
- ⁴ MAX TEMP RATING IS WITH NO OTHER OPTIONS SELECTED.

PHOTOMETRICS

FROST ACRYLIC

Key:

