

# Food Processing Round High Bay: FP-RHB

16" Diameter Suspended High Bay Luminaire

- **Durable Die-Cast Aluminum Housing**
- **160°F (71°C) Maximum Ambient Operating Temperature**
- **Black or White Finishes**
- **Up to 41,340 lumens delivered**
- **NSF Rated**
- **IP66 Rated**
- **0-10V Dimmable standard**
- **Medium Light Distribution**
- **All wedges are adjustable for up or down lighting**



DISCLAIMER: Although KURTZON has prepared the information contained in this document with all due care, KURTZON does not warrant or represent that the information is free from errors or omission. Whilst the information is considered to be true and correct at the date of publication, changes in circumstances after the time of publication may impact on the accuracy of the information. The information may change without notice and KURTZON is not in any way liable for the accuracy of any information printed and stored or in any way interpreted or used.

## ORDERING GUIDE

Series	Size	Qty/LED	CCT/CRI	Voltage	Wedge Position	Finish	Mounting	Options
<b>FP-RHB</b>	<b>16</b>				<b>FWHM80</b>			
<b>FP-RHB</b>	<b>16</b> 16" Diameter	<b>2LEDW</b> 2 LED Wedges <b>3LEDW</b> 3 LED Wedges <b>4LEDW</b> 4 LED Wedges <b>6LEDW</b> 6 LED Wedges	<b>80 CRI:</b> <b>830</b> 3000K <b>840</b> 4000K <b>850</b> 5000K	<b>UNV</b> 120-277 VAC <b>HNV</b> 347-480VAC	<b>FWHM80</b> 80° Beam Angle	<b>WHT</b> White <b>BLK</b> Black	<b>PMB</b> Pendant Mounting Bracket <b>SW</b> Sealed Wireway (3/4" Conduit Hub) <b>EBM</b> Eye Bolt Mount (Standard)	<b>OCC</b> Integrated OCC Sensor <b>CORD</b> Standard cord provided is 4.5Ft 5-Wire Cord. Select cord option and specify length and wire qty for any other cords.
								<div style="background-color: #cccccc; width: 15px; height: 10px; display: inline-block;"></div> Not NSF Certified

Ordering Notes, If Applicable

# Food Processing Round High Bay: FP-RHB

16" Diameter Suspended High Bay Luminaire

## SPECIFICATIONS

**CONSTRUCTION:** Durable die-cast aluminum housing with Polycarbonate optic plates. The unique modular design with thin body and finned heat sinks.


**OPTICS:** Designed for a number of applications, these fixtures offer adjustable light distribution. From leaving all wedges on a plane level to angling all of them up to broaden the reach, the LumaWedge can get the light where it needs to be.

**ELECTRICAL:** Luminaire is paired with a high performance 100-277V AC driver. High-Voltage options available. 50/60 Hz. Power Factor >.9 with THD <.2. A minimum CRI of 80 is standard in 3000K, 4000K, and 5000K color temperatures. All Round High Bay models are 0-10V dimmable and can be paired with a Built-In Motion Sensor.


**INSTALLATION:** Eye Bolt Mount standard for installation. Additional options are Sealed Wireway (3/4" Conduit Hub) or Pendant Mounting Bracket.

**CERTIFICATIONS & LISTINGS:** ETL certified to UL1598. Suitable for Wet Locations. Suitable for Natatoriums. Certified to NSF/ANSI 2 for Splash and Non-food Zones. IP66 Rated.


## DIMENSIONAL DATA




## MOUNTING OPTIONS



**EBM - EYE BOLT MOUNT**  
Eye Loop Mount for Chain/Cable Mount Applications.



**SW - 3/4" CONDUIT ADAPTER** 3/4" Conduit Adapter for Rigid Mount Applications.



**PMB - TRUNNION BRACKET** Trunnion Mount Bracket for Adjustable Surface Mount Applications.

# Food Processing Round High Bay: FP-RHB


16" Diameter Suspended High Bay Luminaire

## ENERGY DATA


LED SPECIFICATION		3000K		4000K		5000K		WEIGHT (lbs.)	AMBIENT OPERATING TEMP	
MODEL	WATTS	LUMENS	EFFICACY	LUMENS	EFFICACY	LUMENS	EFFICACY		MIN	MAX
2LEDW	88	13,545	154 lm/W	13,825	157 lm/W	14,400	164 lm/W	5.29	-25°C (-13°F)	71°C (160°F)
3LEDW	133	20,430	154 lm/W	20,865	157 lm/W	21,735	163 lm/W	6.61		
4LEDW	176	27,075	154 lm/W	27,650	157 lm/W	28,800	163 lm/W	7.49		
6LEDW	254	38,860	153 lm/W	39,685	156 lm/W	41,340	164 lm/W	9.92		

## PHOTOMETRICS


### 2LEDW



### 3LEDW



### 4LEDW



### 6LEDW

